# IXYS

## X3-Class HiPerFET™ Power MOSFET

## IXFH34N65X3

$V_{DSS}$ = 650V
$I_{D25}$ = 34A
$R_{DS(on)}$ ≤ 100mΩ

N-Channel Enhancement Mode
Avalanche Rated




**TO-247 (IXFH)**




G = Gate D = Drain
S = Source Tab = Drain

| Symbol | Test Conditions | Maximum Ratings | |
|---|---|---|---|
| $V_{DSS}$ | $T_J$ = 25°C to 150°C | 650 | V |
| $V_{DGR}$ | $T_J$ = 25°C to 150°C, $R_{GS}$ = 1MΩ | 650 | V |
| $V_{GSS}$ | Continuous | ±20 | V |
| $V_{GSM}$ | Transient | ±30 | V |
| $I_{D25}$ | $T_C$ = 25°C | 34 | A |
| $I_{DM}$ | $T_C$ = 25°C, Pulse Width Limited by $T_{JM}$ | 48 | A |
| $I_A$ | $T_C$ = 25°C | 5 | A |
| $E_{AS}$ | $T_C$ = 25°C | 750 | mJ |
| dv/dt | $I_S \le I_{DM}$, $V_{DD} \le V_{DSS}$, $T_J \le 150°C$ | 50 | V/ns |
| $P_D$ | $T_C$ = 25°C | 446 | W |
| $T_J$ | | -55 ... +150 | °C |
| $T_{JM}$ | | 150 | °C |
| $T_{stg}$ | | -55 ... +150 | °C |
| $T_L$ | Maximum Lead Temperature for Soldering 1.6 mm (0.062 in.) from Case for 10s | 300 | °C |
| $M_d$ | Mounting Torque | 1.13 / 10 | Nm/lb.in |
| Weight | | 6 | g |

| Symbol | Test Conditions ($T_J$ = 25°C, Unless Otherwise Specified) | Characteristic Values Min. | Typ. | Max. | |
|---|---|---|---|---|---|
| $BV_{DSS}$ | $V_{GS}$ = 0V, $I_D$ = 1mA | 650 | | | V |
| $V_{GS(th)}$ | $V_{DS} = V_{GS}$, $I_D$ = 2.5mA | 3.2 | | 5.2 | V |
| $I_{GSS}$ | $V_{GS}$ = ±20V, $V_{DS}$ = 0V | | | ±100 | nA |
| $I_{DSS}$ | $V_{DS} = V_{DSS}$, $V_{GS}$ = 0V | | | 25 | μA |
| | $T_J$ = 125°C | | | 3 | mA |
| $R_{DS(on)}$ | $V_{GS}$ = 10V, $I_D = 0.5 \bullet I_{D25}$, Note 1 | | | 100 | mΩ |

### Features

- International Standard Package
- Low $R_{DS(ON)}$ and $Q_G$
- Avalanche Rated
- Low Package Inductance

### Advantages

- High Power Density
- Easy to Mount
- Space Savings

### Applications

- Switch-Mode and Resonant-Mode Power Supplies
- DC-DC Converters
- PFC Circuits
- AC and DC Motor Drives
- Robotics and Servo Controls

©2021 Littelfuse, Inc.

| Symbol | Test Conditions ($T_J$ = 25°C, Unless Otherwise Specified) | Characteristic Values Min. | Typ. | Max | |
|---|---|---|---|---|---|
| $g_{fs}$ | $V_{DS}$ = 10V, $I_D$ = 0.5 • $I_{D25}$, Note 1 | 13 | 22 | | S |
| $R_{Gi}$ | Gate Input Resistance | | 1.7 | | Ω |
| $C_{iss}$ | $V_{GS}$ = 0V, $V_{DS}$ = 25V, f = 1MHz | | 2025 | | pF |
| $C_{oss}$ | | | 2800 | | pF |
| $C_{rss}$ | | | 2.6 | | pF |
| | **Effective Output Capacitance** | | | | |
| $C_{o(er)}$ | Energy related; $V_{GS}$ = 0V, $V_{DS}$ = 0.8 • $V_{DSS}$ | | 100 | | pF |
| $C_{o(tr)}$ | Time related; $V_{GS}$ = 0V, $V_{DS}$ = 0.8 • $V_{DSS}$ | | 440 | | pF |
| $t_{d(on)}$ | **Resistive Switching Times** | | 24 | | ns |
| $t_r$ | $V_{GS}$ = 10V, $V_{DS}$ = 0.5 • $V_{DSS}$, $I_D$ = 0.5 • $I_{D25}$ | | 10 | | ns |
| $t_{d(off)}$ | $R_G$ = 10Ω (External) | | 47 | | ns |
| $t_f$ | | | 6 | | ns |
| $Q_{g(on)}$ | $V_{GS}$ = 10V, $V_{DS}$ = 0.5 • $V_{DSS}$, $I_D$ = 0.5 • $I_{D25}$ | | 29 | | nC |
| $Q_{gs}$ | | | 11 | | nC |
| $Q_{gd}$ | | | 10 | | nC |
| $R_{thJC}$ | | | | 0.28 | °C/W |
| $R_{thCS}$ | | | 0.21 | | °C/W |

**Source-Drain Diode**

| Symbol | Test Conditions ($T_J$ = 25°C, Unless Otherwise Specified) | Characteristic Values Min. | Typ. | Max | |
|---|---|---|---|---|---|
| $I_S$ | $V_{GS}$ = 0V | | | 34 | A |
| $I_{SM}$ | Repetitive, Pulse Width Limited by $T_{JM}$ | | | 136 | A |
| $V_{SD}$ | $I_F$ = $I_S$, $V_{GS}$ = 0V, Note 1 | | | 1.4 | V |
| $t_{rr}$ | $I_F$ = 17A, -di/dt = 100A/μs | | 150 | | ns |
| $Q_{RM}$ | $V_R$ = 100V | | 1.05 | | μC |
| $I_{RM}$ | | | 14.0 | | A |

Note 1. Pulse test, t ≤ 300μs, duty cycle, d ≤ 2%.

Littelfuse reserves the right to change limits, test conditions and dimensions.

IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents: 4,835,592 4,860,072 4,881,106 4,931,844 5,017,508 5,034,796 5,049,961 5,063,307 5,187,117 5,237,481 5,381,025 5,486,715 6,162,665 6,259,123B1 6,306,728B1 6,404,065B1 6,534,343 6,583,505 6,683,344 6,710,405B2 6,710,463 6,727,585 6,759,692 6,771,478B2 7,005,734B2 7,063,975B2 7,071,537 7,157,338B2

**Fig. 1. Output Characteristics @ $T_J$ = 25ºC**




**Fig. 2. Extended Output Characteristics @ $T_J$ = 25ºC**




**Fig. 3. Output Characteristics @ $T_J$ = 125ºC**




**Fig. 4. $R_{DS(on)}$ Normalized to $I_D$ = 17A Value vs. Junction Temperature**




**Fig. 5. $R_{DS(on)}$ Normalized to $I_D$ = 17A Value vs. Drain Current**




**Fig. 6. Normalized Breakdown & Threshold Voltages vs. Junction Temperature**




©2021 Littelfuse, Inc.

**Fig. 7. Maximum Drain Current vs. Case Temperature**




**Fig. 8. Input Admittance**




**Fig. 9. Transconductance**




**Fig. 10. Forward Voltage Drop of Intrinsic Diode**




**Fig. 11. Gate Charge**




**Fig. 12. Capacitance**




Littelfuse reserves the right to change limits, test conditions and dimensions.

**Fig. 13. Output Capacitance Stored Energy**




**Fig. 14. Forward-Bias Safe Operating Area**




**Fig. 15. Maximum Transient Thermal Impedance**




©2021 Littelfuse, Inc.

**TO-247 Outline**




| SYM | INCHES | | MILLIMETERS | |
|---|---|---|---|---|
| | MIN | MAX | MIN | MAX |
| A | .190 | .205 | 4.83 | 5.21 |
| A1 | .090 | .100 | 2.29 | 2.54 |
| A2 | .075 | .085 | 1.91 | 2.16 |
| b | .045 | .055 | 1.14 | 1.40 |
| b2 | .075 | .087 | 1.91 | 2.20 |
| b4 | .115 | .126 | 2.92 | 3.20 |
| C | .024 | .031 | 0.61 | 0.80 |
| D | .819 | .840 | 20.80 | 21.34 |
| D1 | .650 | .690 | 16.51 | 17.53 |
| D2 | .035 | .050 | 0.89 | 1.27 |
| E | .620 | .635 | 15.75 | 16.13 |
| E1 | .545 | .565 | 13.84 | 14.35 |
| e | .215 BSC | | 5.45 BSC | |
| J | -- | .010 | -- | 0.25 |
| K | -- | .025 | -- | 0.64 |
| L | .780 | .810 | 19.81 | 20.57 |
| L1 | .150 | .170 | 3.81 | 4.32 |
| øP | .140 | .144 | 3.55 | 3.65 |
| øP1 | .275 | .290 | 6.99 | 7.37 |
| Q | .220 | .244 | 5.59 | 6.20 |
| R | .170 | .190 | 4.32 | 4.83 |
| S | .242 BSC | | 6.15 BSC | |

IXYS
A Littelfuse Technology

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.

Littelfuse reserves the right to change limits, test conditions and dimensions.