




ohne Ansaughaube - *without hood*








Anforderungsstufe 1
performance level 1

Kontaktbereich vergoldet
mating area gold plating


Anschlussbereich verzinnt 4-6 µm
terminal area 4-6 µm tin plating

Koplanarität der Anschlüsse ≤ 0,1 mm
coplanarity area of termination ≤ 0,1 mm


Verpackt im Gurt in Anlehnung an DIN IEC 60286-3
tape on reel packaging according to DIN IEC 60286-3
Verpackungseinheit: 650 Stück
packaging unit: 650 pcs



Abspulrichtung - *reel off direction*



Leiterplatten-Layout für SMT
PCB-Layout for SMT



Für die Anforderung nach PG 9 der LV214
(Koshiri-Sicherheit)
For the requirement of the LV214 PG 9
(Koshiri-security)

Information:

Tolerances

All Dimensions in mm

Scale 5:1

Copyright by ERNI GmbH
Proprietary notice pursuant to ISO 16016 to be observed.

All rights reserved.
Only for Information.
To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.

Subject to modification without prior notice.
Drawing will not be updated.

Designation
M 1,27 SRC P, 6-polig KS
M 1,27 SRC P, 6-pin KS

www.ERNI.com

474817 I

A2

Index	Date
c	29.08.2018

Class SRCP