Features

Regulated Converter

- 2MOPP, 250VAC working voltage isolation
- Clearance and creepage distance >8mm
- Up to 10kVDC reinforced insulation
- IEC/EN/UL 60601 certified with CB Report (3rd Ed. Safety, 4th Ed. EMC)
- -40°C to +75°C operation, no derating
- 2:1 wide input range


RECOM
DC/DC Converter

REM6E

6 Watt 2:1 Input DIP24 or SMD Single & Dual Output

3 YEAR warranty





2MOPP
250VAC

CAN/CSA-C22.2 No. 60601-1:14 certified
ANSI/AAMI ES60601-1 certified
EN60601-1 certified
IEC60601-1 certified
IEC60601-1-2 compliant
EN55032 compliant

Description

The REM6E series of medical grade regulated DC/DC converters feature reinforced 250VAC continuous working isolation with >8mm creepage/clearance. The compact DIP24/SMD package offers industry standard pinouts with tightly regulated single/dual outputs and UVLO, SCP and OCP. The operating ambient temperature range is from -40°C to +75°C without derating. The converters are UL marked and certified to CB, IEC, EN and ANSI/AAMI 60601 3rd. Ed. Safety and 4th Ed. EMC medical standards. The low 1µA leakage current complies with medical applied part B, BF and CF limits as defined by IEC60601-1.

Selection Guide

Part Number	Input Voltage Range [VDC]	Output Voltage [VDC]	Output Current [mA]	Efficiency typ.(1) [%]	Max. Capacitive Load (2) [µF]
REM6E-xx09S (3,4,5)	9-18 / 18-36 / 36-75	9	667	81 / 82 / 83	2200
REM6E-xx12S (3,4,5)	9-18 / 18-36 / 36-75	12	500	82 / 83 / 84	2200
REM6E-xx15S (3,4,5)	9-18 / 18-36 / 36-75	15	400	83 / 84 / 84	2200
REM6E-xx24S (3,4,5)	9-18 / 18-36 / 36-75	24	250	83 / 84 / 85	1000
REM6E-xx09D (3,4,5)	9-18 / 18-36 / 36-75	±9	±335	81 / 82 / 83	±2200
REM6E-xx12D (3,4,5)	9-18 / 18-36 / 36-75	±12	±250	82 / 83 / 84	±2200
REM6E-xx15D (3,4,5)	9-18 / 18-36 / 36-75	±15	±200	83 / 84 / 84	±2200

Notes:

Note1: Efficiency is tested at nominal input and full load at +25°C ambient
Note2: Max Cap Load is tested at nominal input and full resisitive load

Model Numbering

REM6E- ___ ___ /R /A / ___ /

- Output Power
- nom. Input Voltage
- Output Voltage
- Single or Dual
- Isolation (3)
- Pinning
- Case Style or CTRL Option (4)
- UVLO Option (5)

Notes:

Note3: add suffix „/R8“ for 8kVDC or „/R10“ for 10kVDC isolation (DIP24 only)
if SMD package is used, always add suffix „/R6“ for 6kVDC isolation
Note4: add suffix „/CTRL“ for fitted CTRL pin (DIP24 only)
if SMD package is used do not add suffix „/CTRL“, CTRL pin is always mounted
Note5: add suffix „/X1“ for Under Voltage Lockout Option

Ordering Examples

REM6E-1209S/R8/A	= 12Vin, 9Vout, Single, 8kVDC Isolation and „A“ pinning, DIP24
REM6E-1212D/R10/A/CTRL	= 12Vin, 12Vout, Dual, 10kVDC Isolation, „A“ pinning, with CTRL pin
REM6E-1209S/R6/A/SMD	= 12Vin, 9Vout, Single, 6kVDC Isolation, „A“ pinning, SMD with CTRL pin
REM6E-2412D/R10/A/CTRL/X1	= 24Vin, 12Vout, Dual, 10kVDC Isolation, „A“ pinning, DIP24, CTRL pin and UVLO Option

Specifications (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)


BASIC CHARACTERISTICS

Parameter	Condition		Min.	Typ.	Max.
Internal Input Filter					Pi-type
Input Voltage Range	nom. Vin = 12VDC nom. Vin = 24VDC nom. Vin = 48VDC		9VDC 18VDC 36VDC	12VDC 24VDC 48VDC	18VDC 36VDC 75VDC
Under Voltage Lockout (UVLO) („/X1" version)	nom. Vin= 12VDC	DC-DC ON DC-DC OFF		 7.9VDC	9VDC
	nom. Vin= 24VDC	DC-DC ON DC-DC OFF		 16.7VDC	18VDC
	nom. Vin= 48VDC	DC-DC ON DC-DC OFF		 34.3VDC	36VDC
Input Current	nom. Vin = 12VDC nom. Vin = 24VDC nom. Vin = 48VDC			650mA 320mA 150mA	
Quiescent Current	nom. Vin = 12VDC nom. Vin = 24VDC nom. Vin = 48VDC				35mA 25mA 7mA
Minimum Load (7)				10%	
Start-up time				0.6ms	
Rise time				0.45ms	
Hold-up time				0.6ms	
ON/OFF CTRL	DC-DC ON DC-DC OFF				Open or 0VDC<V_{CTRL}<1.2VDC Short or 4.8VDC<V_{CTRL}<12VDC
Input Current of CTRL Pin	V_{CTRL}=5VDC			25mA	
Standby Current	DC-DC OFF				350µA
Internal Operating Frequency			120kHz		
Output Ripple and Noise (6)	20MHz BW				150mVp-p

Notes:

Note6: Measurements are made with a 0.1µF MLCC across output. (low ESR)

ON/OFF CTRL Option




R1
470Ω

continued on next page


Specifications (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

Efficiency vs. Output Load

REM6E-1212S




REM6E-2412S




Efficiency vs. Input Voltage
(@ full Load)

REM6E-1212S



REM6E-2412S



REGULATIONS		
Parameter	**Condition**	**Value**
Output Accuracy		±1.5% typ.
Line Regulation	low line to high line, full load	±0.3% max.
Load Regulation (7)	10% to 100% load	0.5% typ.
Cross Regulation	dual output only	±5.0% max.
Transient Response	25% load step change	5ms

Notes:


Note7: Operation below 10% load will not harm the converter, but specifications may not be met

continued on next page


Specifications (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

Deviation vs. Load

REM6E-1212S



REM6E-2412S



PROTECTIONS

Parameter	Type				Value
Short Circuit Protection (SCP)	below 100mΩ				continuous, hiccup mode, automatic recovery
Isolation Voltage [8]	I/P to O/P	DIP24	"/R8" suffix	tested for 1 second rated for 1 minute	8kVDC 4kVAC/60Hz
			"/R10" suffix	tested for 1 second rated for 1 minute	10kVDC 5kVAC/60Hz
		SMD	"/R6" suffix	rated for 1 minute	6kVDC
Isolation Resistance					10GΩ min.
Isolation Capacitance					20pF typ.
Insulation Grade					reinforced
Leakage Current					0.8µA typ. / 1µA max.
Means of Protection	250VAC working voltage				2MOPP
Medical Device Classification					built-in power supply
Internal	clearance/creepage				>8mm
External	clearance/creepage				>8mm

Notes:

Note8: For repeat Hi-Pot testing, reduce the time and/or the test voltage

Note9: Refer to local safety regulations if input over-current protection is also required. Recommended fuse: slow blow type

ENVIRONMENTAL


Parameter	Condition		Value
Operating Temperature Range	full load @ natural convection 0.1m/s (see graph)		-40°C to +75°C
Maximum Case Temperature			+105°C
Temperature Coefficient			±0.02%/K typ. / ±0.05%/K max.
Thermal Impedance	0.1m/s, horizontal		20K/W
Operating Altitude			3000m
Operating Humidity	non-condensing		5% - 95% RH max.
Pollution Degree			PD2
MTBF	according to MIL-HDBK-217F, G.B.	+25°C +75°C	2100 x 10^3 hours 620 x 10^3 hours

continued on next page

Specifications (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

Derating Graph

(@ Chamber and natural convection 0.1m/s)



SAFETY AND CERTIFICATIONS		
Certificate Type (Safety)	**Report / File Number**	**Standard**
Medical Electric Equipment, General Requirements for Safety and Essential Performance	E314885	CAN/CSA-C22.2 No. 60601-1:14, 3rd Edition: 2014 ANSI/AAMI ES60601-1:2012
Medical Electric Equipment, General Requirements for Safety and Essential Performance (CB Scheme)	E314885	IEC60601-1:2005, 3rd Edition + AM1:2012
Medical Electric Equipment, General Requirements for Safety and Essential Performance	WD-SE-R-180524-A0	EN60601-1:2006 + A12:2014 IEC60601-1:2005, 3rd Edition + AM1:2012
RoHS 2		RoHS 2011/65/EU + AM2015/863

EMC Compliance	**Condition**	**Standard / Criterion**
Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement	with external filter refer to ***„EMC Filtering“***	EN55032, Class A and B
Information technology equipment - Immunity characteristics - Limits and methods of measurement		EN55024:2010 + A1:2015
ESD Electrostatic discharge immunity test	Air ±8kV, Contact ±4kV	IEC61000-4-2:2009, Criteria A
Radiated, radio-frequency, electromagnetic field immunity test	3V/m	IEC61000-4-3:2006 + A2:2010, Criteria A
Fast Transient and Burst Immunity	DC Power Port: ±1kV	IEC61000-4-4:2012, Criteria A
Surge Immunity	DC Power (Output) Port: ±0.5kV	IEC61000-4-5:2014 + A1:2017, Criteria A
Immunity to conducted disturbances, induced by radio-frequency fields	DC Power (Output) Port: 3V	IEC61000-4-6:2013 + C1:2015, Criteria A
Power Magnetic Field Immunity	50Hz, 1A/m	IEC61000-4-8:2010, Criteria A
Medical electrical equipment Part 1-2: Electromagnetic disturbances – Requirements and tests	with external filter	EN60601-1-2:2015 IEC60601-1-2:2014
Industrial, scientific and medical equipment – Radio frequency disturbance characteristics – Limits and methods of measurement		EN55011:2016+A1:2017, Class B
ESD Electrostatic discharge immunity test	Air ±15kV, Contact ±8kV	IEC61000-4-2:2008, EN61000-4-2:2009
Radiated, radio-frequency, electromagnetic field immunity test	10V/m	IEC61000-4-3:2006+A1:2007+A2:2010 EN61000-4-3:202006+A2:2010
Fast Transient and Burst Immunity	DC Power Port: ±2kV	IEC/EN61000-4-4:2012
Surge Immunity	DC Power (Output) Port: ±1kV	IEC/EN61000-4-5:2014+A1:2017
Immunity to conducted disturbances, induced by radio-frequency fields	DC Power (Output) Port: 3V, 6V	IEC61000-4-6:2013, EN61000-4-6:2014
Power Magnetic Field Immunity	50Hz, 30A/m	IEC61000-4-8:2009, EN61000-4-8:2010


continued on next page

Specifications (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)


EMC Filtering Suggestions according to EN55032

Class A

Single output



Dual output





Component List Class A

MODEL	C1	C2	C3	C4	L1
REM6E-12xxS/R/A	4.7µF/50V	N/A	100pF/12kV	N/A	3.3µH
REM6E-24xxS/R/A	10µF/100V		150pF/12kV		
REM6E-48xxS/R/A					
REM6E-12xxD/R/A	4.7µF/50V		100pF/12kV	100pF/12kV	
REM6E-24xxD/R/A	10µF/100V		150pF/12kV	150pF/12kV	
REM6E-48xxD/R/A					


Class B


Single output





Dual output





Component List Class B

MODEL	C1	C2	C3	C4	L1	CMC
REM6E-12xxS/R/A	4.7µF/50V	4.7µF/50V	220pF/12kV	N/A	50µH	N/A
REM6E-24xxS/R/A	10µF/100V	10µF/100V	220pF/12kV			
REM6E-48xxS/R/A			330pF/12kV		N/A	1mH
REM6E-12xxD/R/A	4.7µF/50V	4.7µF/50V	220pF/12kV	220pF/12kV	50µH	N/A
REM6E-24xxD/R/A	10µF/100V	10µF/100V	220pF/12kV	220pF/12kV		
REM6E-48xxD/R/A			330pF/12kV	330pF/12kV	N/A	1mH


Specifications (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

DIMENSION and PHYSICAL CHARACTERISTICS

Parameter	Type	Value
Material	baseplate case potting	non-conductive black plastic, (UL94 V-0) non-conductive black plastic, (UL94 V-0) silicone, (UL94 V-0)
Dimension (LxWxH)	DIP24 SMD	31.8 x 20.3 x 10.2mm 31.8 x 20.3 x 10.9mm
Weight		14g typ.

Dimension Drawing (mm)

DIP24




Pin Connections

Pin #	Single	Dual
1	CTRL (4)	CTRL (4)
2	-Vin	-Vin
11	NC	-Vout
14	+Vout	+Vout
16	-Vout	Com
22	+Vin	+Vin
23	+Vin	+Vin

Tolerance:
xx.x ± 0.5mm
xx.xx ± 0.25mm

SMD



Pin Connections

Pin #	Single	Dual
1	CTRL	CTRL
2	-Vin	-Vin
3, 4, 5, 9, 10	NC	NC
11	NC	-Vout
12, 13, 15	NC	NC
14	+Vout	+Vout
16	-Vout	Com
20, 21, 24	NC	NC
22	+Vin	+Vin
23	+Vin	+Vin

Tolerance:
xx.x ± 0.5mm
xx.xx ± 0.35mm

Specifications (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

PACKAGING INFORMATION			
Parameter	**Type**		**Value**
Packaging Dimension (LxWxH)	tube	DIP24	520.0 x 22.7 x 18.3mm
		SMD	530.0 x 30.3 x 19.2mm
Packaging Quantity	tube		15pcs
Storage Temperature Range			-55°C to +125°C
Storage Humidity			95% RH max.

The product information and specifications may be subject to changes even without prior written notice.The product has been designed for various applications; its suitability lies in the responsibility of each customer. The products are not authorized for use in safety-critical applications without RECOM's explicit written consent. A safety-critical application is an application where a failure may reasonably be expected to endanger or cause loss of life, inflict bodily harm or damage property. The applicant shall indemnify and hold harmless RECOM, its affiliated companies and its representatives against any damage claims in connection with the unauthorized use of RECOM products in such safety-critical applications.