IGBT - Field Stop
650 V, 40 A

FGH40N65UFDTU, FGH40N65UFDTU-F085

Description

Using novel field stop IGBT technology, ON Semiconductor's field stop IGBTs offer the optimum performance for Automotive Chargers, Inverter, and other applications where low conduction and switching losses are essential.

Features

- High Current Capability
- Low Saturation Voltage: $V_{CE(sat)}$ = 1.8 V @ I_C = 40 A
- High Input Impedance
- Fast Switching
- Qualified to Automotive Requirements of AEC−Q101 (FGH40N65UFDTU−F085)
- These Devices are Pb−Free and are RoHS Compliant

Applications

- Automotive Chargers, Converters, High Voltage Auxiliaries
- Inverters, PFC, UPS

ON Semiconductor®

www.onsemi.com

V_{CES}	I_C
650 V	40 A





TO−247−3LD
CASE 340CK

MARKING DIAGRAM



Industrial Automotive

$Y	= ON Semiconductor Logo
&Z	= Assembly Plant Code
&3	= Numeric Date Code
&K	= Lot Code
FGH40N65UFD / FGH40N65UFDTU	= Specific Device Code

ORDERING INFORMATION

See detailed ordering and shipping information on page 2 of this data sheet.

© Semiconductor Components Industries, LLC, 2015

ABSOLUTE MAXIMUM RATINGS

Symbol	Description		Ratings	Unit
V_{CES}	Collector to Emitter Voltage		650	V
V_{GES}	Gate to Emitter Voltage		±20	V
I_C	Collector Current	T_C = 25°C	80	A
		T_C = 100°C	40	A
I_{CM} (Note 1)	Pulsed Collector Current	T_C = 25°C	120	A
P_D	Maximum Power Dissipation	T_C = 25°C	290	W
		T_C = 100°C	116	W
T_J	Operating Junction Temperature		−55 to +150	°C
T_{STG}	Storage Temperature Range		−55 to +150	°C
T_L	Maximum Lead Temp. for Soldering Purposes, 1/8” from Case for 5 Seconds		300	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Repetitive rating: Pulse width limited by max. junction temperature.

THERMAL CHARACTERISTICS

Symbol	Parameter	Typ.	Unit
$R_{\theta JC}$ (IGBT)	Thermal Resistance, Junction to Case	0.43	°C/W
$R_{\theta JC}$ (Diode)	Thermal Resistance, Junction to Case	1.45	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	40	°C/W

PACKAGE MARKING AND ORDERING INFORMATION

Part Number	Top Mark	Package	Packing Method	Qty per Tube
FGH40N65UFDTU	FGH40N65UFD	TO−247	Tube	30
FGH40N65UFDTU−F085*	FGH40N65UFDTU	TO−247	Tube	30

*Qualified to Automotive Requirements of AEC−Q101.

ELECTRICAL CHARACTERISTICS OF THE IGBT (T_C = 25°C unless otherwise noted)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
OFF CHARACTERISTICS						
BV_{CES}	Collector to Emitter Breakdown Voltage	V_{GE} = 0 V, I_C = 250 μA	650	–	–	V
$\Delta BV_{CES} / \Delta T_J$	Temperature Coefficient of Breakdown Voltage	V_{GE} = 0 V, I_C = 250 μA	–	0.6	–	V/°C
I_{CES}	Collector Cut−Off Current	V_{CE} = V_{CES}, V_{GE} = 0 V	–	–	250	μA
I_{GES}	G−E Leakage Current	V_{GE} = V_{GES}, V_{CE} = 0 V	–	–	±400	nA
ON CHARACTERISTICS						
$V_{GE(th)}$	G−E Threshold Voltage	I_C = 250 μA, V_{CE} = V_{GE}	4.0	5.0	6.5	V
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	I_C = 40 A, V_{GE} = 15 V,	–	1.8	2.4	V
		I_C = 40 A, V_{GE} = 15 V, T_C = 125°C	–	2.0	–	V
DYNAMIC CHARACTERISTICS						
C_{ies}	Input Capacitance	V_{CE} = 30 V, V_{GE} = 0 V, f = 1 MHz	–	1860	–	pF
C_{oes}	Output Capacitance		–	200	–	pF
C_{res}	Reverse Transfer Capacitance		–	65	–	pF
SWITCHING CHARACTERISTICS						
$T_{d(on)}$	Turn−On Delay Time	V_{CC} = 400 V, I_C = 40 A, R_G = 10 Ω, V_{GE} = 15 V, Inductive Load, T_C = 25°C	–	23	–	ns
T_r	Rise Time		–	35	–	ns
$T_{d(off)}$	Turn−Off Delay Time		–	126	–	ns
T_f	Fall Time		–	26	60	ns
E_{on}	Turn−On Switching Loss		–	1.28	–	mJ
E_{off}	Turn−Off Switching Loss		–	0.50	–	mJ
E_{ts}	Total Switching Loss		–	1.78	–	mJ
$T_{d(on)}$	Turn−On Delay Time	V_{CC} = 400 V, I_C = 40 A, R_G = 10 Ω, V_{GE} = 15 V, Inductive Load, T_C = 125°C	–	21	–	ns
T_r	Rise Time		–	39	–	ns
$T_{d(off)}$	Turn−Off Delay Time		–	131	–	ns
T_f	Fall Time		–	72	–	ns
E_{on}	Turn−On Switching Loss		–	1.62	–	mJ
E_{off}	Turn−Off Switching Loss		–	0.79	–	mJ
E_{ts}	Total Switching Loss		–	2.41	–	mJ
Q_g	Total Gate Charge	V_{CE} = 400 V, I_C = 40 A, V_{GE} = 15 V	–	119	–	nC
Q_{ge}	Gate to Emitter Charge		–	14	–	nC
Q_{gc}	Gate to Collector Charge		–	64	–	nC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

ELECTRICAL CHARACTERISTICS OF THE DIODE (T_C = 25°C unless otherwise noted)

Symbol	Parameter	Test Conditions		Min	Typ	Max	Unit
V_{FM}	Diode Forward Voltage	I_F = 20 A	T_C = 25°C	–	1.80	2.6	V
			T_C = 125°C	–	1.71	–	
T_{rr}	Diode Reverse Recovery Time	I_F = 20 A, di_F/dt = 200 A/μs	T_C = 25°C	–	65	–	ns
			T_C = 125°C	–	215	–	
Q_{rr}	Diode Reverse Recovery Charge		T_C = 25°C	–	145	–	nC
			T_C = 125°C	–	775	–	

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

TYPICAL PERFORMANCE CHARACTERISTICS



Figure 1. Typical Output Characteristics



Figure 2. Typical Output Characteristics



Figure 3. Typical Saturation Voltage Characteristics



Figure 4. Transfer Characteristics



Figure 5. Saturation Voltage vs. Case Temperature at Variant Current Level



Figure 6. Saturation Voltage vs. V_{GE}

TYPICAL PERFORMANCE CHARACTERISTICS (Continued)



Figure 7. Saturation Voltage vs V_{GE}



Figure 8. Saturation Voltage vs V_{GE}



Figure 9. Capacitance Characteristics



Figure 10. Gate Charge Characteristics



Figure 11. SOA Characteristics



Figure 12. Turn−on Characteristics vs. Gate Resistance

TYPICAL PERFORMANCE CHARACTERISTICS (Continued)



Figure 13. Turn−off Characteristics vs. Gate Resistance



Figure 14. Turn−on Characteristics vs. Collector Current



Figure 15. Turn−off Characteristics vs. Collector Current



Figure 16. Switching Loss vs. Gate Resistance



Figure 17. Switching Loss vs. Collector Current



Figure 18. Turn Off Switching SOA Characteristics

TYPICAL PERFORMANCE CHARACTERISTICS (Continued)



Figure 19. Forward Characteristics



Figure 20. Reverse Current



Figure 21. Stored Charge



Figure 22. Reverse Recovery Time



Figure 23. Transient Thermal Impedance of IGBT

MECHANICAL CASE OUTLINE
PACKAGE DIMENSIONS

ON Semiconductor®

TO−247−3LD SHORT LEAD
CASE 340CK
ISSUE A

DATE 31 JAN 2019



DIM	MILLIMETERS		
	MIN	NOM	MAX
A	4.58	4.70	4.82
A1	2.20	2.40	2.60
A2	1.40	1.50	1.60
b	1.17	1.26	1.35
b2	1.53	1.65	1.77
b4	2.42	2.54	2.66
c	0.51	0.61	0.71
D	20.32	20.57	20.82
D1	13.08	~	~
D2	0.51	0.93	1.35
E	15.37	15.62	15.87
E1	12.81	~	~
E2	4.96	5.08	5.20
e	~	5.56	~
L	15.75	16.00	16.25
L1	3.69	3.81	3.93
ØP	3.51	3.58	3.65
ØP1	6.60	6.80	7.00
Q	5.34	5.46	5.58
S	5.34	5.46	5.58

NOTES: UNLESS OTHERWISE SPECIFIED.

A. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.
B. ALL DIMENSIONS ARE IN MILLIMETERS.
C. DRAWING CONFORMS TO ASME Y14.5 - 2009.
D. DIMENSION A1 TO BE MEASURED IN THE REGION DEFINED BY L1.
E. LEAD FINISH IS UNCONTROLLED IN THE REGION DEFINED BY L1.

GENERIC
MARKING DIAGRAM*



XXXX = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
ZZ = Assembly Lot Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	**98AON13851G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**TO−247−3LD SHORT LEAD**	**PAGE 1 OF 1**

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2018

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales