| linear dimension(Tolerances Standard GB/T 14486-2008) | | | | | | | | — | ▱ | ⊥ |
|---|---|---|---|---|---|---|---|---|---|---|
| variable range | to 6 | over 6 to 10 | over 10 to 30 | over 30 to 60 | over 60 to 100 | over 100 to 160 | over 160 to | to 10 | over 10 to 100 | over 100 to |
| tolerance | ±0.20 | ±0.30 | ±0.50 | ±0.70 | ±1.00 | ±1.30 | ±1.60 | 0.10 | 0.30 | 0.60 |




PCB Layout







| UL/CUL 技术 参数 UL/CUL Technical Data | | | |
|---|---|---|---|
| 等 级 Use Group | B | C | D |
| 额定电压 Rated Voltage [V] | 300 | - | 300 |
| 额定电流 Rated Current [A] | 30 | - | 30 |
| 接线范围 Wire Range 单/多芯线 Solid/Stranded [AWG] | 26-10 | | |
| 耐电压 Withstanding Voltage | 1600V/1Min | | |
| IEC 技术参数 IEC Technical Data | | | |
| 过电压类别 Overvoltage Category | III | III | II |
| 污染等级 Contamination Class | 3 | 2 | 2 |
| 额定电压 Rated Voltage [V] | 630 | 1000 | 1000 |
| 额定电流 Rated Current [A] | 32 | 32 | 32 |
| 额定冲击电压 Impulse withstand voltagea [KV] | 8 | 8 | 8 |
| 导线截面积 Conductor cross section 硬质/柔性导线 Solid/ flexible [mm²] | 4 | | |
| 材 料 Material | | | |
| 绝缘材料 Insulation Material | PA66 | | |
| 阻燃等级 Imflammability | UL94V-0 | | |
| 导体材料 Contactor Material | 铜合金 Copper alloy | | |
| 导体表面镀层 Contactive Coating | 镀锡 Sn Plated | | |
| 一般参数 Other Data | | | |
| 间距 Pitch [mm] | 9.52 | | |
| 极数 Poles [P] | 02~24 | | |
| 剥线长度 Stripping Length [mm] | 7 | | |
| 螺丝 Screw/扭矩 Torque(Max) [N.m] | M3/0.5 | | |
| 工作温度 Operating temperatur [°C] | -40~+105 | | |
| 引针尺寸 Pin Dimensions [mm] | 0.80x1.15 | | |
| PCB板孔径 PCB Hole Diameter [mm] | 1.70 | | |

DB910 — 9.52 — XXP — C — S/P

(Series No.) (Pitch) (Poles) Slotted/Phillips

(Color):GN:(Green), BK:(Black), BU:(Blue), RD:(Red), GY:(Gray)
OG:(Orange), WT:(White), YL:(Yellow), CR:(Clear)

| | | | | | |
|---|---|---|---|---|---|
| APPD: JTing Chen 2023.03.17 | DORABO | 宁波地博电气有限公司 Ningbo Dorabo Electric CO., Ltd | | | |
| CHKD: Duck Mao 2023.03.17 | NAME: DB910-9.52-XXP-C-P | | | | |
| DRFT: Steven Lu 2023.03.17 | SIZE: A4 | mm (inch) | REV | T0-1 | |
| | TYPE: CUSTOMER_DRAWING | SCALE: 1:1 | SHEET | 1/1 | |